

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**



IFW

PATENT  
KEL01 P-133

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Ian Hill  
Serial No. : 10/821,542  
Filed : April 9, 2004  
For : LOCKING MECHANISM FOR A LINEAR ACTUATOR

Commissioner for Patents  
P.O. Box 1450  
Alexandria VA 22313-1450

Dear Sir:

CERTIFICATE OF MAIL

I certify that the attached return postcard, Claim of Priority, and a certified copy of United Kingdom Patent Application No. 0308409.2 are being deposited with the United States Postal Service as first class mail in an envelope addressed to:

Commissioner for Patents  
P.O. Box 1450  
Alexandria VA 22313-1450

on June 9, 2004.

Catherine S. Collins  
Reg. No. 37 599  
Van Dyke, Gardner, Linn & Burkhart, LLP  
P.O. Box 888695  
Grand Rapids, MI 49588-8695  
(616) 975-5502

CSC:lmse  
Enclosures

**THIS PAGE BLANK (USPTO)**





**PATENT**  
**KEL01 P-133**

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Ian Hill  
Serial No. : 10/821,542  
Filed : April 9, 2004  
For : LOCKING MECHANISM FOR A LINEAR ACTUATOR

Commissioner for Patents  
P.O. Box 1450  
Alexandria VA 22313-1450

Dear Sir:

CLAIM OF PRIORITY

Applicant hereby claims the priority benefits under the provisions of 35 U.S.C. 119, basing said claim of priority on United Kingdom patent Application No. 0308409.2, filed April 22, 2003.


In accordance with the provisions of 35 U.S.C. 119 and 37 C.F.R. 1.55(a), a certified copy of the above listed United Kingdom patent application is attached.

Respectfully submitted,

IAN HILL

By: Van Dyke, Gardner, Linn & Burkhardt, LLP

Dated: June 9, 2004

  
Catherine S. Collins  
Registration No. 37 599  
Suite 207  
2851 Charlevoix Drive, S.E.  
Grand Rapids, Michigan 49546  
(616) 975-5500

CSC:lmse  
Enclosure



**THIS PAGE BLANK (USPTO)**



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh; references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed   
Dated 4 May 2004

**THIS PAGE BLANK (USPTO)**



## Patents Form 1/77

Patents Act 1977  
(Rule 16)THE PATENT OFFICE  
PS  
11 APR 200311APR03 E799707-1 D02950  
P01/7700 0.00-0308409.2

## Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQBY FAX: 01633 814444  
26 PAGES.

## 1. Your reference

MOC/AW

## 2. Patent application number

(The Patent Office will fill in this part)

0308409.2

11 APR 2003

## 3. Full name, address and postcode of the or of each applicant (underline all surnames)

IAN HILL

1 SANDY ROAD

SHEPTOWN

NEWRY

COUNTY DOWN

BT34 3LB, NORTHERN IRELAND

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

8609273001

## 4. Title of the invention

LOCKING MECHANISM FOR A LINEAR ACTUATOR

## 5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

9 UNIVERSITY STREET

BELFAST

BT7 1FY

NORTHERN IRELAND

Patents ADP number (if you know it)

7774417001

## 6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)Date of filing  
(day / month / year)

## 7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

## 8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))


No

Patents Form 1/77

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form ☐  
Description **20**  
Claim(s) ☐  
Abstract ☐  
Drawing(s) **4**



10. If you are also filing any of the following, state how many against each item.

Priority documents ☐  
Translations of priority documents ☐  
Statement of inventorship and right to grant of a patent (Patents Form 7/77) ☐  
Request for preliminary examination and search (Patents Form 9/77) ☐  
Request for substantive examination (Patents Form 10/77) ☐  
Any other documents ☐  
(please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

*Alan Wallace*

Date

11/4/03

ALAN WALLACE, AGENT FOR APPLICANT

12. Name and daytime telephone number of person to contact in the United Kingdom

ALAN WALLACE 02890 236000

**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

**Notes**

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.  
b) Write your answers in capital letters using black ink or you may type them.  
c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.  
d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.  
e) Once you have filled in the form you must remember to sign and date it.  
f) For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

## LOCKING MECHANISM FOR A LINEAR ACTUATOR

The present invention relates to linear actuators and in particular to a locking mechanism for use therewith.

- 5 The invention is particularly, but not exclusively, suited for use with hydraulic linear actuators.

Hydraulic linear actuators are well known and are often referred to as hydraulic cylinders or hydraulic rams.

- 10 In some applications failure of the actuator or its associated pipework, or accidental operation by an operator can result in personal injury or damaged equipment. Hydraulic check valves can be used to safeguard against pipework failure but such check  
15 valves do not protect against a piston, seal or other failure internal to the actuator.

- It is known to provide an additional mechanical locking device which may be either manually or automatically  
20 operable. If the locking device is manually operated, then its operation relies upon the operator correctly inserting the locking device. A simple prop as used under the raised body of a tipper type lorry is an example of a manually inserted locking device.

- 25 Automatic locking devices often require extra control devices and actuators and this results in size and cost penalties. An example of an automatic locking device is the 'scotch' lever used on vertically stroking hydraulic presses. Whichever conventional approach is  
30 adopted, it can be rendered useless by either human error or mechanical/electrical failure.

It is considered therefore that there is a need for an improved locking mechanism for linear actuators.

Accordingly a first aspect of the invention provides a locking mechanism for a linear actuator comprising a piston rod arranged for linear movement between a fully retracted state and a fully extended state, the locking mechanism comprising a piston follower coupled to the piston rod for movement therewith, and a latching member moveable between a non-locked state and at least one locked state in which the latching member obstructs the movement of the piston follower such that the piston rod is prevented from adopting the fully retracted state.

Preferably, the latching member is pivotable with respect to the actuator. Preferably, the latching member is biased to adopt a locked state. For example, a spring, or other biasing means, may be provided between the latching member and the actuator. The latching member may comprise one or more latching bars pivotably mounted on, or coupled to, the actuator. In the illustrated embodiment, the latching member comprises two spaced-apart latching bars, each being pivotably coupled to a respective opposite side of the actuator.

Preferably, the latching member includes one or more bearing surfaces for engagement with the piston follower. Advantageously, the latching member includes a plurality of bearing surfaces, each arranged to engage with the piston follower, or a respective part thereof, in a respective locked state, wherein the location of each bearing surface in the respective locked state is arranged to halt the movement of the

## BEST AVAILABLE COPY

3

piston rod at a respective state of extension between the fully extended and fully retracted states. In the illustrated embodiment, each latching bar is shaped to define a plurality of respective bearing surfaces.

5

Preferably, the latching member includes one or more catching surfaces for engagement with the piston follower, as the latching member moves towards the, or a respective locked state, so that the, or a  
10 respective, bearing surface is held in the path of the piston follower. In the preferred embodiment, the or each bearing surface is associated with a respective catching surface. Advantageously, the or each bearing surface is substantially perpendicular with its  
15 respective catching surface. This may be arranged by providing a respective substantially L-shaped recess in the latching member.

Preferably, the piston follower is arranged for  
20 corresponding linear movement with the piston rod. In the preferred embodiment, the piston follower comprises one or more bar, or rod, which is substantially parallel with the piston rod. In the illustrated embodiment, the piston follower comprises two spaced-  
25 apart rods located adjacent respective opposite sides of the actuator and arranged for engagement with a respective latching bar. Advantageously, a guide or support member may be provided for guiding the movement of the piston follower (or parts thereof) and provided  
30 support thereto (or to parts thereof).

In the preferred embodiment, the locking mechanism further includes one or more secondary actuators

arranged to actuate the latching member, or a respective part thereof, from the at least one locked state to the non-locked state. Advantageously, the actuator (main actuator) and the or each secondary  
5 actuator are inter-linked so that they may each be operated by a common operating circuit, e.g. hydraulic circuit. Preferably, the common operating circuit is operable in a first mode, in which the piston rod of main actuator is caused to extend, a second mode, in  
10 which the piston rod of the main actuator is caused to retract and the respective piston rods of the or each secondary actuator may extend, or a third mode, in which the respective piston rods of both the main and secondary actuators extend.

15

In the preferred embodiment, the main actuator is a double acting actuator having a piston chamber divided into a retract side and an extend side, the retract side being inter-linked with the secondary actuator(s)  
20 so that operating fluid may be supplied to the secondary actuator(s) from said retract side to cause the respective piston rods of the secondary actuator(s) to extend. In this arrangement, said third mode of operation is effected by supplying operating fluid,  
25 under pressure, to both sides of the main actuator simultaneously.

Other advantageous aspects and features of the invention will be apparent to those ordinarily skilled  
30 in the art upon review of the following description of a specific embodiment of the invention and with reference to the accompanying drawings.

## BEST AVAILABLE COPY

5

Embodiments of the invention are now described by way of example and with reference to the accompanying drawings in which like numerals are used to indicate like parts and in which:

5

Figure 1 is a perspective view of a hydraulic linear actuator including a first embodiment of a locking mechanism according to the invention;

- 10 Figure 2 is a perspective view of a hydraulic linear actuator including a second embodiment of a locking mechanism according to the invention;

- Figure 3 is an alternative perspective view of the  
15 hydraulic linear actuator and locking mechanism of Figure 2;

- Figure 4 is a perspective view of a hydraulic linear actuator including a third embodiment of a locking  
20 mechanism according to the invention;

- Figure 5 is an alternative perspective view of the hydraulic linear actuator and locking mechanism of Figure 4;

25

Figure 6 is a further alternative perspective view of the hydraulic linear actuator and locking mechanism shown in Figures 2 and 3;

- 30 Figure 7 is a table illustrating the operation of a valve switch suitable for use by the locking mechanisms of Figures 1 to 6; and

6

Figure 8 is a schematic of a hydraulic circuit suitable for use by the locking mechanisms of Figures 1 to 6.

Referring now to Figure 1 of the drawings, there is shown, generally indicated as 10, a hydraulic linear actuator comprising a piston chamber 12, piston 14 (not visible in Figure 1 but shown schematically in Figure 8) and piston rod 16. In the example of Figure 1, a rod eye 18 is provided at the free external end of the piston rod 18 for connecting the rod 18 to an article (not shown) that requires actuation by the actuator 10. It will be understood that a variety of alternative conventional connectors may be used in place of the rod eye 18.

15

The actuator 10 is generally conventional in its configuration and operation. The piston rod 18 is linearly actuatable between a fully retracted state, in which the piston rod 16 is retracted within the piston chamber 12 to a maximum extent, and a fully extended state in which the piston rod 16 extends from the piston chamber 12 to a maximum extent. In Figure 1 the piston rod 16 is shown in an intermediate state between the fully extended and fully retracted states. The state of the piston rod 16 is controlled by the flow of hydraulic fluid, usually oil, into and out of the piston chamber 12. For use with the preferred embodiments described hereinafter, the actuator 10 is assumed to be a double-acting actuator in which the state of the piston rod 16 is controlled by the flow of hydraulic fluid into and out of two fluid inlet/outlet ports (not shown in Figure 1), wherein the piston 14 is located between the two ports.



Hydraulic actuators of the type described above are commonly referred to as hydraulic cylinders (because the piston chamber 12 is usually generally cylindrical as shown in Figure 1) or hydraulic rams.

Figure 1 also illustrates a first embodiment of a locking mechanism according to the invention. The locking mechanism is comprised of two main components, namely a piston follower 20 and a latch assembly 22.

The piston follower 20 comprises a rod or bar (or any other suitable member) which coupled to the piston rod 16 for movement therewith. At least a portion of the piston follower 20 is located externally of the piston chamber 12 so that it may be engaged by the latch assembly as is described in more detail below. In the embodiment of Figure 1, the piston follower 20 comprises two rods 21, 21' each of which is connected to, or adjacent, the free end of piston rod 16 so that the rods 21, 21' are substantially parallel with the piston rod 16. This may be achieved, by way of example, by means of a connecting bar or plate 24 which also, conveniently, may carry the rod eye 18.

When the piston rod 16 moves linearly between the fully retracted and fully extended states, or between any of the infinite number of intermediate states therebetween, the piston follower 20 moves linearly by a corresponding amount in the same direction. Each of the rods 21, 21' has a respective free end 26, 26' (only one visible in Figure 1) located externally of

the piston cylinder 12 for engagement with the latching assembly 22.

Advantageously, a guide or support member may be provided for guiding the movement of the piston follower 20. In Figure 1, a guide member in the form of a plate 28 is carried by the exterior of the piston cylinder 12 and is shaped to define a respective aperture or channel through which the respective rods 21, 21' pass. The plate 28 helps to reduce flexing or bending of rods 21, 21' which may occur when under load.

It will be understood that, in alternative embodiments (not illustrated) the piston follower may comprise only one, or more than two, rods or other follower members.

The latching assembly 22 comprises one or more latch members 30 comprising at least one respective bearing surface for engagement with the piston follower 20 in order to limit the piston follower's linear travel. In the Figure 1 embodiment, the latching assembly comprises a latch member 30 having two substantially parallel latching bars 31, 31' each comprising a respective bearing surface 32, 32'.

The latching bars 31, 31' are operatable between a non-locked state (as shown in Figure 1) in which the latching bars 31, 31' do not interfere with the movement of the piston follower 20, and a locked state (shown in Figures 2 and 5), in which the latching bars 31, 31', and in particular the respective bearing surfaces 32, 32', obstruct the movement of the piston

BEST AVAILABLE COPY

9

follower 20 thereby preventing the piston rod 16 from reaching its fully retracted state.

- Preferably, the latching member 30 is pivotable with respect to the piston cylinder 12. In Figure 1, the latching bars 31, 31' are pivotably mounted, at respective pivot points 33, 33', on a butt member 34 located at the base of the piston cylinder 12 (i.e. the end of the cylinder opposite that from which the piston rod 16 extends). The latching bars 31, 31' are therefore pivotable between the non-locked state and the locked state about their respective pivot points 33, 33'.
- 15 In the preferred embodiment, the latching member 30 is biased towards the locked state. In the embodiment of Figure 1, a respective spring 36, 36' (only one visible in Figure 1) is provided between each latching bar 31, 31' and the butt 34 and is arranged to urge the
- 20 respective latching bar 31, 31' into the locked state. It will be understood that other conventional biasing means (not illustrated) may alternatively be used for this purpose and that the biasing means need not necessarily be connected to the butt 34 as long as it
- 25 acts on the latching member 30 in the manner described. Moreover, in the embodiment of Figure 1, the latching bars 31, 31' are joined together by a cross bar 40 such that their movement is unitary. In such an embodiment, there is no need to provide a respective biasing
- 30 spring, or the like, for each latching bar 31, 31'.

In an alternative embodiment (not illustrated), the latching member is arranged to be urged towards the

10

locked state under the influence of gravity and no biasing is required.

The latching member 30 is arranged so that the latching  
5 bars 31, 31' are disposed at opposite sides of the  
piston chamber 12 and are arranged for engagement with  
a respective rod 21, 21' of the piston follower when in  
the locked state. Each latching bar 31, 31' is shaped  
to define a catching surface 38, 38' for engaging with  
10 the piston follower 20 as the latching member 30 moves  
into the locked state thereby halting the movement of  
the latching member 30 so that the respective bearing  
surface 32, 32' is located in the path of the  
respective rod 21, 21'. Preferably, the bearing  
15 surface 32, 32' and its respective catching surface 38,  
38' are substantially perpendicular to one another and  
are provided by a substantially L-shaped recess formed  
in the respective latching bar 31, 31'.

20 In use, when the piston rod is in the fully retracted  
state, the latching member 30 is prevented from  
adopting the locked state by the piston follower 20 (as  
shown in Figure 1). As the piston rod 16 is extended  
towards the fully extended state, the piston follower  
25 20 moves clear of the latching member 30 thereby  
allowing it to adopt the locked state under the action  
of the springs 36, 36'. In the locked state, the  
catching surfaces 38, 38' engage against the respective  
rods 21, 21' thereby positioning the respective bearing  
30 surfaces 32, 32' in the respective path of the free  
ends 26, 26' of the respective rods 21, 21'. This may  
best be appreciated from Figure 5. It will be seen  
that the piston rod 16 is prevented from returning to

## BEST AVAILABLE COPY

11

the fully retracted state since the movement of the piston follower 20 is obstructed by the latching member 30, and in particular the bearing surfaces 32, 32'. Hence, in the locked state, the latching member 30 restricts, or limits, the movement of the piston rod 16.

Figures 2, 3 and 6 show an alternative embodiment which is generally similar to the embodiment of Figure 1 and in which like numerals are used to indicate like parts. In Figures 2, 3 and 6, for illustration purposes only, the latching bars 131, 131' are not interconnected. Further, each latching bar 131, 131' is shaped to define more than one bearing surface 132, 132' and more than one catching surface 138, 138'. This allows the latching mechanism 130 to adopt more than one locked state. Preferably, each bearing surface 132, 132' has a respective associated catching surface 138, 138' which, advantageously, are substantially perpendicular to one another. In Figures 2 and 3, prefixes A and B are used to denote associated bearing and catching surfaces. Associated bearing and catching surfaces 132, 132', 138, 138' may be defined by respective substantially L-shaped recesses formed in the respective latching bars 131, 131'. From an alternative viewpoint, the bearing and catching surfaces 132, 132', 138, 138' may be formed by providing the latching bars 131, 131' with a serrated or toothed edge.

30

Hence, the latching member 130 adopts one of a plurality of locked states in sequence depending on the extension of the piston rod 16. In each progressive

12

locked state, a respective bearing surface 132, 132' prevents the respective rods 21, 21' from retracting further than a respective intermediate state, the respective intermediate states being progressively  
5 further away from the fully retracted state. Hence, the location of the in use bearing surface 132, 132' in the path of the rods 20, 20' varies depending on the extension of the piston rod 16. This restricts the amount by which the piston rod 16 can retract in the  
10 event of failure. The amount by which the piston rod 16 can retract in the event of failure is effectively determined by the length of the catching surfaces 138, 138'.

15 By way of example and with reference to Figure 2, the latching bar 131' is shown in a first locked state in which catching surface A138' engages with the free end 26' of rod 21' thereby holding bearing surface A132' in the path of rod 21'. The travel of rod 21' in a  
20 direction towards the fully retracted state is thus restricted - the piston rod 16 would be prevented from reaching the fully retracted state by engagement of the end 26' of rod 21' and the bearing surface A132'. As the piston rod 16 extends towards the fully extended  
25 state, the end 26' of rod 21' moves clear of catching surface A138'. Latching bar 131' then pivots about pivot point 33', under the action of spring 36', until catching surface B138' engages with rod 21' thereby holding bearing surface B132' in the path of rod 21'.  
30 Hence, the latching bar 131' adopts a second locked state (not illustrated) in which the travel of piston rod 16 is further restricted in that, when the end 26' of rod 21' engages with bearing surface B132', the

## BEST AVAILABLE COPY

13

piston rod 16 is held further from the fully retracted state that it is in the first locked state. Similarly, as the piston rod 16 extends still further, the latching bar 131' adopts a third locked state in which bearing surface C132' is located in the path of rod 21'. In the third locked state the travel of piston rod 16 is still further restricted in that, when the end 26' of rod 21' engages with bearing surface C132', the piston rod 16 is held still further from the fully retracted state.

It will be seen, therefore, that as the piston rod 16 extends, the location of the in use bearing surface 132' varies between locked states such that the piston 16 is prevented from travelling towards the fully retracted state past a respective intermediate state which is progressively further from the fully retracted state. In the illustrated embodiments, this is achieved by arranging the latching bar 131' such that the respective distance between the respective bearing surfaces A132', B132', C132' and pivot point 33' increases.

Hence, the latching member 30, 130 automatically adopts a locked state as the piston rod 16 extends. In the event of hydraulic or other failure, the piston rod 16 the travel of the piston rod 16 towards the fully retracted state is restricted by the latching member 30, 130.

In one embodiment (not illustrated) the latching member 30, 130 may be returned to the non-locked state manually. Preferably, however, one or more release

14 ~~\_\_\_\_\_~~

actuators, and in particular, hydraulic actuators are provided for this purpose.

5 In Figure 1, the latching member 30 is unitary (since latching bars 31, 31' are mechanically interconnected by cross bar 40) and so one release actuator 42 is provided. The release actuator 42 is arranged to act on the latching member 30, conveniently on cross bar 40, such that extension of the actuator 42 moves the  
10 latching member 30 to the non-locked state. The release actuator 42 is preferably a linear hydraulic actuator and may be the same general type as actuator 10, although dual ports are not required.

15 Figures 4 and 5 show an alternative embodiment exhibiting features of both the embodiments of Figure 1 and of Figures 2 and 3. The embodiment of Figures 4 and 5 is generally similar to the embodiments already described and similar numerals are used to indicate  
20 like parts. In Figures 4 and 5, the latching member 130 has a serrated or toothed end similar to that of the Figure 2, 3 and 6 embodiment, although the latching bars 131, 131' are mechanically interconnected by a cross bar 40 similarly to the embodiment of Figure 1.  
25 Hence, a single release actuator 42 may also be used in the embodiment of Figures 4 and 5. In the embodiment of Figures 2, 3 and 6, a respective release actuator 42, 42' is provided for each latching bar 131, 131'.

30 The, or each, hydraulic actuator 42, 42' is advantageously operable by a hydraulic circuit (not shown in Figures 1 to 6) which is integral with the



15

hydraulic circuit (not shown in Figures 1 to 6) used to operate the main actuator 10.

A suitable hydraulic circuit 50 for operating the main  
5 actuator 10 and the, or each, release actuator 42, 42'  
is shown schematically in Figure 8. The circuit 50  
includes a hydraulic fluid (typically oil) source 52  
and sink 54. The circuit further includes valve  
switches SV1, SV2 for controlling the flow of hydraulic  
10 fluid to and from the hydraulic actuators 10, 42, 42'.

Hydraulic actuator 10 is shown schematically in Figure  
8 and includes two fluid ports P1, P2 by which  
hydraulic fluid may flow into and out of the piston  
15 chamber 12 via fluid lines 56, 58. The chamber 12 is  
divided into two sections, S1 ("extend side") and S2  
("retract side"), by the piston 14. Fluid flow into P1  
causes a build up of fluid pressure in section S1 of  
the chamber 12 and this exerts a force on piston 14  
20 which causes piston rod 16 to extend. As the piston 14  
extends, fluid flows out of P2. Similarly, fluid flow  
into P2 causes a build up of fluid pressure in section  
S2 of the chamber 12 and this exerts a force on piston  
14 which causes piston rod 16 to retract.

25

A schematic representation of the, or each, release  
actuator 42, 42' is also shown in Figure 8 (only one  
shown). The actuator 42, 42' has a fluid port P3 by  
which hydraulic fluid may flow into and out of the  
30 piston chamber 44 via fluid line 60. Fluid flow into  
P3 causes a build up of fluid pressure behind the  
piston 48 (i.e. on the side of the piston 48 opposite  
the piston rod 46) and this exerts a force on piston 48

which causes piston rod 46 to extend. Unlike the main actuator 10, actuators 42, 42' are not (at least in the illustrated embodiment) double acting actuators.

Retraction of the piston rod 46 may therefore be effected by any suitable means. For example, after a reduction in fluid pressure behind the piston 48 by an outflow of hydraulic fluid from port P3, piston rod 46 may be retracted under the influence of gravity (depending on the in use orientation of the actuator 42, 42'), and/or under the action of the latching member 30, 130 as it adopts the locked state, and/or under the action of a return mechanism (not shown) such as a spring.

In the preferred embodiment port P3 is fed from, or in fluid communication with, the forward, or retract side (section S2) of chamber 12 (i.e. the side of chamber 12 fed by P2). Hence, a build up of fluid pressure in section S2 of chamber 12 causes fluid to be supplied to chamber 44 via P3. This causes a build up of pressure behind piston 48 which, in turn, causes piston rod 46 to extend. When piston rod 16 retracts, piston rod 46 is caused to extend provided there is a sufficient build up of fluid pressure in section S2 to cause fluid to be fed to the chamber 44.

The respective states of valves SV1, SV2 are controllable by a switch mechanism (not shown) which may adopt one of three switch states. These are illustrated in Figure 7 as states A, B and C. In state A, SV1 is open to allow fluid to be supplied into piston chamber 12 via port P1. SV2 is closed to prevent fluid from being fed to P2, but allows fluid to

17

flow from P2 and to return to the sink 54. Hence, in switch state A, piston rod 16 extends.

In switch state A, the piston rod 16 extends in normal manner and, as piston rod 16 extends, the latching member 30, 130 will adopt a locking state as described above. When it is desired to retract the piston rod 16, and assuming that no failure has occurred (i.e. that the rods 21, 21' are not in engagement with the bearing surfaces 32, 32', 132, 132'), the switch mechanism is operated to cause the valves SV1, SV2 to adopt switch state C.

In switch state C, SV2 is open to allow fluid to be supplied into piston chamber 12 via port P2. SV1 is closed to prevent fluid from being fed to P1, but allows fluid to flow from P1 and to return to the sink 54. Hence, in switch state C, piston rod 16 retracts. Also, because chambers 12, 44 are interconnected, fluid flow into chamber 12 via port 2 results in fluid flow into chamber 44 via port 3. As a result, piston rod 46 extends. The extension of piston rod 46 causes the respective actuator 42, 42' to move the latching member 30, 130 to the non-locked state. The arrangement is such that, in this normal mode of operation, the, or each, actuator 42, 42' has moved the latching member 30, 130 into the non-locked state before the piston follower 20 would have otherwise engaged with one or more bearing surfaces 32, 32', 132, 132'. Hence, the latching member 30, 130 is moved to the non-locked state before or during retraction of the piston rod 16 and does not interfere with the retraction of the piston rod 16.

However, should a failure occur such that the piston follower 20 is in engagement with one or more bearing surfaces 32, 32', 132, 132', then such engagement prevents, or inhibits, the latching member 30, 130 from moving to the non-locked state in the manner described above. It is therefore preferred to cause the main piston rod 16 to extend slightly to disengage the piston follower 20 from the latching member 30, 130.

10

In the preferred embodiment, this is achieved by causing the switch mechanism to adopt switch state B. In switch state B, both valves SV1, SV2 are open to allow fluid to be supplied to both sides of piston chamber 12 via both ports P1, P2. Hydraulic fluid is supplied to both sides of piston chamber 12 simultaneously and at substantially the same pressure. This results in a net out-stroke (extension) of piston rod 16 due to differential piston sizes (the force exerted on piston 14 from section S1 will be greater than the force exerted on piston 14 from section S2. This is because the surface area of piston 14 on which fluid in section S2 can act is smaller than the surface area of piston 14 on which fluid in section S1 can act (because of the piston rod 16)). This has the effect of disengaging the piston follower 20 and the latching member 30, 130.

The pressure of fluid supplied to P2 is sufficiently high to ensure that fluid is simultaneously fed to chamber 44 via port 3 and this causes the, or each, piston rod 46 to extend thereby moving the latching member 30, 130 to the non-locked state. The switching

mechanism may then be returned to state C to allow the piston rod 16 to be retracted normally.

5 The provision of switch state B and the corresponding operation of the hydraulic circuit 50 and actuators 10, 42, 42' is advantageous in that it ensures that the piston follower 20 does not become jammed against the latching bars 31, 31', 131, 131' thereby preventing the latch member 30, 130 from being moves to the non-locked  
10 state. This can occur as a result of a "race" between the retracting piston rod 16 and the extending piston rod 48: in order to extend the piston rod 48 fluid pressure must be built up in section S2 of piston chamber 12. However, should the resultant force  
15 exerted on piston 14 be tending to retract piston rod 16, sufficient pressure may not be built up until the actuator 10 encounters a stop, which could take the form of engagement between piston follower 20 and the latching bars 31, 31', 131, 131'.

20 The switching mechanism may be manually operatable or automatically operable as is convenient. In either case, in the preferred embodiment, to disengage the piston follower from the latching member, state B is  
25 adopted (typically for a few seconds) followed by state C to retract the piston rod 16.

It will be appreciated from the foregoing that the locking mechanism described herein provides an  
30 automatic locked state which substantially prevents any significant unwanted retraction of the main piston rod 16 as a result of any failure of the main actuator 10.



Moreover, the locking mechanism may not readily be moved to the non-locked state through operator error.

A further advantage of the preferred embodiment is that the additional actuator(s) 42, 42' and associated hydraulic circuitry required to release the latching member 30, 130 do not cause significant penalties in terms of cost and size. The locking mechanism and main actuator 10 may be formed as an integral unit, sharing a common hydraulic circuit (which may be housed in the butt 34 and or chamber 12 body) and requires no additional hydraulic connections or components other than would be required by a conventional hydraulic actuator. Hence the actuator 10 with the locking mechanism of the invention may be used as a direct replacement for conventional actuators.

The invention is described herein in the context of a double acting, dual port hydraulic actuator. It will be understood, however, that at least some aspects of the invention may also be used with non-hydraulic actuators, e.g. spring-biased actuators, or with single port and/or single acting actuators. Further, alternative hydraulic fluid supply arrangements for actuators 10, 42, 42' other than that depicted in Figure 8 may be employed.

The invention is not limited to the embodiments described herein which may be modified or varied without departing from the scope of the invention.



1/4





**THIS PAGE BLANK (USPTO)**



2/4



**THIS PAGE BLANK (USPTO)**




**THIS PAGE BLANK (USPTO)**

4/4

Value/ Switch Pattern	SV1	SV2
A	X	
B	X	X
C		X

FIGURE 7.



**FIGURE 8**

THIS PAGE BLANK (USPTO)